

COMPACT 600 DISPLAY

The Compact 600 with glass door is practical and reliable, designed for kitchens and serving areas with limited space.

Its space-optimised design in GN dimensions (2/1 GN depth) and a height of just under 2 metres allows it to fit where most other devices of this kind cannot.

The glass door and integrated LED light provides a clear overview, while the optimised cooling system guarantees energy-efficient and stable operation, automatic defrosting and rapid temperature recovery – even with frequent door openings.

The intelligent controller with a user-friendly control panel optimises operational reliability and ensures low energy consumption.

A full-length handle integrated into the door ensures good ergonomics and efficient operation, whilst the rounded corners and removable magnetic door gaskets make it easy to maintain optimal hygiene.

The exterior material can be adapted to suit the use and purpose – choose between stainless steel and white-lacquered steel.

Delivered in the well-known high quality from Gram Professional, ensuring stable operation and long service life.

Standard equipment:

- Exterior in stainless or white painted steel
- Interior made in one piece vacuum-formed PS with moulded shelf supports
- 4 nylon coated wire shelves (anti-tilt)
- Right hinged reversible door with lock
- LED lighting
- Removable heavy-duty door gasket
- Adjustable legs (135-200 mm) or castors (128 mm)

Optional extras:

- Additional wire shelves (coated or stainless)
- Perforated shelves in stainless steel
- Left hinged-door
- Various castor and leg options



GLASS DOOR REFRIGERATOR +2/+12°C

MODEL	GR600
ITEM NUMBER STAINLESS STEEL	946010321
ITEM NUMBER WHITE	946010320
VOLUME (liter, gross/net)	580 / 421
NUMBER OF SHELVES	4
ENERGY EFFICIENCY CLASS / EEI	D / 70,1
ENERGY CONSUMPTION (kwh/year)	912
SOUND LEVEL (db(A))	45
COOLING CAPACITY AT -10°C (W)	413
COOLING CAPACITY AT -25°C (W)	–
CLIMATE CLASS	4 (30°C/55% RH)
DIMENSIONS W x D x H (m)	695x868x2010
GROSS WEIGHT (kg)	114
REFRIGERANT / FILLING	R600a / 0,062 kg
GWP / Co2 EQUIVALENT	3 / 0,000174 t
CONNECTION	230 V, 50 Hz / 1,83A
CONNECTION LOAD (w)	276

COMPACT 600 DISPLAY

