

COMPACT 200 DISPLAY

The Compact 200 with glass door is practical and reliable, designed for kitchens and serving areas with limited space.

The glass door and integrated LED light provides a clear overview, while the optimised cooling system ensures energy-efficient and stable operation, automatic defrosting and rapid temperature recovery – even with frequent door openings.

With a small footprint and low height, it fits in anywhere, and the low noise level makes it ideal for installation under tabletops in kitchens, bars and cafés.

The intelligent controller with a user-friendly control panel optimises operational reliability and ensures low energy consumption.

A full-length handle integrated into the door ensures good ergonomics and efficient operation, whilst the rounded corners and removable magnetic door gaskets make it easy to maintain optimal hygiene.

The exterior material can be adapted to suit the use and purpose – choose between stainless steel and white-lacquered steel.

Delivered in the well-known high quality from Gram Professional, ensuring stable operation and long service life.

Standard equipment:

- Exterior in stainless or white painted steel
- Interior made in one piece vacuum-formed PS with moulded shelf supports
- 2 nylon coated wire shelves (anti-tilt)
- Right hinged reversible door with lock
- LED lighting
- Removable heavy-duty door gasket
- Adjustable front 'legs' and roller on the back

Optional extras:

- Additional wire shelves (coated or stainless)
- Perforated shelves in stainless steel
- Left hinged-door
- Different castor or leg options



	GLASS DOOR REFRIGERATOR +2/+12°C	GLASS DOOR FREEZER -10/-22°C
MODEL	GR200	GF200
ITEM NUMBER STAINLESS STEEL	942010321	942030221
ITEM NUMBER WHITE	942010320	942030220
VOLUME (liter, gross/net)	128 / 78	128 / 78
NUMBER OF SHELVES	2	2
ENERGY EFFICIENCY CLASS / EEI	A / 20,8	B / 34,7
ENERGY CONSUMPTION (kwh/year)	413	895
SOUND LEVEL (db(A))	33,7	38
COOLING CAPACITY AT -10°C (W)	177	–
COOLING CAPACITY AT -25°C (W)	–	159
CLIMATE CLASS	4 (30°C/55% RH)	3 (25°C/60% RH)
DIMENSIONS W x D x H (m)	595x667x830	595x642x830
GROSS WEIGHT (kg)	49	49
REFRIGERANT / FILLING	R600a / 0,031 kg	R600a / 0,043 kg
GWP / Co2 EQUIVALENT	3 / 0,000093 t	3 / 0,000129 t
CONNECTION	230 V, 50 Hz / 0,38 A	230 V, 50 Hz / 0,64 A
CONNECTION LOAD (w)	77	149

COMPACT 200 DISPLAY

