G+ BY GRAM PROFESSIONAL

MADE IN DENMARK

COMPACT 200





The Compact 200 is robust and reliable, designed for kitchens and serving areas with limited space.

The optimised cooling system ensures energy-efficient and stable operation, automatic defrosting and rapid temperature recovery – even with frequent door openings.

With a small footprint and low height, it fits in anywhere, and the low noise level makes it ideal for installation under tabletops in kitchens, bars and cafés.

The intelligent controller with a user-friendly control panel optimises operational reliability and ensures low energy consumption.

A full-length handle integrated into the door ensures good ergonomics and efficient operation, whilst the rounded corners and removable magnetic door gaskets make it easy to maintain optimal hygiene.

The exterior material can be adapted to suit the use and purpose, choose between stainless steel and white-lacquered steel.

Delivered in the well-known high quality from Gram Professional, ensuring stable operation and long service life.

Standard equipment:
- Exterior in stainless or white painted steel
- Interior made in one piece vacuum-formed PS with moulded shelf supports
- 2 nylon coated wire shelves (anti-tilt)
- Right hinged reversible door with lock
- Removable heavy-duty door gasket
- Adjustable front 'legs' and roller on the back

Optional extras:
- Additional wire shelves (coated or stainless)
- Perforated shelves in stainless steel
- Left hinged-door
- Various castor and leg options

	REFRIGERATOR +2/+12°C	FREEZER -25/-5°C
MODEL	R200	F200
ITEM NUMBER STAINLESS STEEL	942000121	942020221
ITEM NUMBER WHITE	942000120	942020220
VOLUME (liter, gross/net)	128 / 78	128 / 78
NUMBER OF SHELVES	2	2
ENERGY EFFICIENCY CLASS / EEI	A+ / 11,4	B / 30,7
ENERGY CONSUMPTION (kwh/year)	227	871
SOUND LEVEL (db(A))	30,1	37
COOLING CAPACITY AT -10°C (W)	120	–
COOLING CAPACITY AT -25°C (W)	–	178
CLIMATE CLASS	4 (30°C/55% RH)	4 (30°C/55% RH)
DIMENSIONS W x D x H (m)	595x642x830	595x642x830
GROSS WEIGHT (kg)	44	46
REFRIGERANT / FILLING	R600a / 0,031 kg	R600a / 0,033 kg
GWP / Co2 EQUIVALENT	3 / 0,000093 t	3 / 0,000099 t
CONNECTION	230 V, 50 Hz / 0,28 A	230 V, 50 Hz / 0,78 A
CONNECTION LOAD (w)	62	120

COMPACT 200

