

COMPACT 400 DISPLAY

The Compact 400 with glass door is practical, reliable and space-efficient, designed for kitchens and serving areas with limited space.

The glass door and integrated LED light provides a clear overview, while the optimised cooling system guarantees energy-efficient and stable operation, automatic defrosting and rapid temperature recovery – even with frequent door openings.

The intelligent control system with a user-friendly control panel optimises operational reliability and ensures low energy consumption.

With a full-length handle built into the door, you are assured of good ergonomics and efficient operation, and the rounded corners and removable magnetic door gaskets make it easy to maintain optimal hygiene.

The exterior material can be adapted to suit the use and purpose – choose between stainless steel and white-lacquered steel.

Delivered in the well-known high quality from Gram Professional, ensuring stable operation and long service life.

Standard equipment:

- Exterior in stainless or white painted steel
- Interior made in one piece vacuum-formed PS with moulded shelf supports
- 5 nylon coated wire shelves (anti-tilt)
- Right hinged reversible door with lock
- LED lighting
- Removable heavy-duty door gasket
- Adjustable legs (135-200 mm) or castors (128 mm)

Optional extras:

- Additional wire shelves (coated or stainless)
- Perforated shelves in stainless steel
- Left hinged-door
- Various castor and leg options



	GLASS DOOR REFRIGERATOR +2/+12°C	GLASS DOOR FREEZER -10/-22°C
MODEL	GR400	GF400
ITEM NUMBER STAINLESS STEEL	944010321	944030221
ITEM NUMBER WHITE	944010320	944030220
VOLUME (liter, gross/net)	359 / 266	359 / 266
NUMBER OF SHELVES	5	5
ENERGY EFFICIENCY CLASS / EEI	D / 64,7	B / 17,16
ENERGY CONSUMPTION (kwh/year)	677	1231
SOUND LEVEL (db(A))	34,2	37,7
COOLING CAPACITY AT -10°C (W)	210	–
COOLING CAPACITY AT -25°C (W)	–	200
CLIMATE CLASS	4 (30°C/55% RH)	3 (25°C/60% RH)
DIMENSIONS W x D x H (m)	595x667x1875	595x667x1875
GROSS WEIGHT (kg)	84	91
REFRIGERANT / FILLING	R600a / 0,051 kg	R600a / 0,047 kg
GWP / Co2 EQUIVALENT	3 / 0,000153 t	3 / 0,000141 t
CONNECTION	230 V, 50 Hz / 0,41 A	230 V, 50 Hz / 1,17A
CONNECTION LOAD (w)	103	166

COMPACT 400 DISPLAY

