

1/1 GN

+12°C

-5°C



Gastro C2 Refrigerated counter with extended refrigeration

Item number: 940210120

Gastro C2 is an energy efficient, durable, and reliable refrigerated counter build for demanding professional use with high demands for temperature stability.

WORK ENVIRONMENT, CLEANING AND EFFICIENT USE

The counter is as standard equipped with 1 left-hand door and 1 right-hand door and ergonomic door handles. It is constructed with rounded corners. The doors have removable sealing strips for easy and efficient cleaning. The counter is delivered as standard with stainless wire shelves. It can be configured with drawers – 1/2 or 1/3 as needed.

SUSTAINABILITY

Besides being energy efficient and thus having low operational costs, the counter is produced locally in Denmark with focus on minimizing the impact of the environment, social responsibility and with energy from renewable energy sources.

SECURITY


The counter comes with up to 5 years warranty, and it has a ventilated cooling system, which ensures good temperature stability and air distribution, and that the temperature is quickly restored after door openings.

WHAT IS G+?

G+ is Gram Professional ApS's brand for professional refrigeration and freezer products for food storage.

'G' symbolizes that we have roots in the Danish Gram Group.

'+' symbolizes that innovation is a part of our DNA and that we continuously develop, so that we always live up to the customers' needs and expectations.



MADE IN DENMARK

TECHNICAL SPECIFICATIONS

Product name	C2 G FT DL DR L2 E	Energy efficiency class / EEI	A / 20,9
Product type	Professional refrigerated counter 1/1 GN	Energy consumption (kWh/year)	476 kWh
Temperature range	-5/+12°C	Sound level	45,1 dB(A)
Volume (gross / net)	345 / 255 L	Warranty	Up to 5 years
Dimensions (WxDxH)	1289x700x885/950 mm	Climate class	5 (40°C/40% RH)
Material (exterior / interior)	Stainless steel / Stainless steel	Door type	Isolated doors
Gross weight	124 kg	Legs	H = 135/200 mm
Refrigerant / charge	R290 / 0,097 kg	Number of shelves (max. number)	2 per compartment / (20) – GN-measure 325x530 mm (WxD)
GWP and Co2 equivalent	3 / 0,000291 t	Equipped with	1 left-hand door and 1 right-hand door, 4 stainless wire shelves.
Refrigeration capacity at -10°C	225 W	Variation options	Additional wire shelves (stainless), castors instead of legs, drawers instead of door, worktop with 50 mm raised rear upstand.
Connection (supply voltage)	230 V, 50 Hz / 1A		
Connection load	207 W		